

Reversible Soil Compactors

weber*mt*

CR

The Colours of Progress

CR 1



CR 1 R



The CR 1 provides a comfortable hydraulic control, to reverse machine direction plus many other distinctive features that make it the ideal entry into the Weber *mt* product line for rental machinery fleet owners and professional users. With a working width of 400 mm (16"), its centrifugal force of 20 kN (4500 lbs) and compaction depth down to 30 cm (12") (according to the type of soil), the CR 1 is a versatile machine which delivers high working speeds for superior performance and increased efficiency.

The CR 1 can be equipped with a gasoline or diesel engine.

Little compactor - great features:

- Forward and reverse travel
- Infinitely variable hydraulic control for precise work even under adverse conditions
- Robust protection frame to prevent the engine from getting damaged. Diesel version with engine guard.
- Low-maintenance design due to self-adjusting centrifugal clutch
- Quick loading, also by means of fork lift trucks, due to large, fixed lifting lug
- Excellent price-/performance ratio

Available optional extras:

- Polyurethane pad
- Wheel kit

The CR 1 and its technical data.

Type		CR 1	CR 1 R	CR 1 Hd
Operating weight according to CECE	kg (lbs)	118 (260)	103 (227)	104 (229)
Centrifugal force	kN (lbs)	20 (4500)	20 (4500)	20 (4500)
Frequency	Hz (rpm)	90 (5400)	90 (5400)	90 (5400)
Operating width	mm (in.)	400 (16)	400 (16)	400 (16)
Engine		Diesel	4-stroke gasoline	4-stroke gasoline
Engine type		Lombard. 15 LD 225	Robin EY 20	Honda GX 160
Engine output according to DIN 70020	kW/HP	3,5/4,7	3,4/4,6	4,0/5,5

We reserve the right to alter these specifications

